



Golvkedje-  
brädan

Produkt  
datablad  
2016

### Teknisk information Golvkedjebrädan

Thickness	13 & 14 mm
Width	194 & 162
Length	2027, 2200, 2000 & 2281
Wearlayer thickness	app. 2,5 & 3,5
Weight (kg/m <sup>2</sup> )	app. 8,0
Taber Abraser/Lacquer's wear resistance* prEN 13696 abrasion penetration Lacq. (revs)	>4000
abrasion penetration Matt Lacq.. (revs)	>3500
abrasive wear (mg/100revs)	app. 2,5
Reduction of sound weighted index index "footfall" to the room below. NF EN ISO 140-8 / Acc to NF EN ISO 717-2, "Lw in dB with 2 mm Tarkofoam/flex II	17
Formaldehyde emission EN 13986	E1
Reaction to Fire EN 13501	Dfl
Thermal insulation value (RT m <sup>2</sup> K/W)	
board only	0,101
with rag felt	0,121
with 2 mm Tarkofoam/flex II	0,141
Installation **	Floating/Glue down
Underfloor heating compatible***	Maximum floor surface temperature 27oC with self-regulating under-floor heat system.

\* Data show results with new components according to 2006 update.  
Method not applicable for brushed products due to the structured surface.  
\*\* Contact your flooring supplier for further infomation.  
\*\*\* Not suitable for the woodspecies beech and maple.

Golvkedjebrädan	Lacquer 2-loc	Matt Lacq. 2-loc	Lacquer 5 tech
-----------------	------------------	---------------------	-------------------

	Lacquer 2-loc	Matt Lacq. 2-loc	Lacquer 5 tech
3 - strip 14 x 2027 x 194 mm			
Oak Nature	*	*	
1 - strip 13 x 2200/2000 x 162 mm			
Oak Robust	*		
3 - strip 14 x 2281 x 194 mm			
Oak (nature grade)			*

Tillverkad i Sverige av



THE ULTIMATE  
FLOORING EXPERIENCE



GOLVKEDJAN - YRKESMÄN ÖVER HELA LANDET